

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

1.0 Identification

1.1 Product Identifier

Product Name: Poloplaz Water Based Paint

Application of the substance/the preparation: Waterborne Paint

1.2 Relevant identified uses of the substance or mixture: Finishes, Coatings and Related Materials:
For Professional Use Only.

1.3 Supplier:

Poloplaz

1 Paradise Park Road

Jacksonville, AR 72076

Telephone: (501) 985-1172

www.poloplaz.com

1.4 Emergency contact:

Infotrac #: 1-800-535-5053

2.0 Hazards Identification

GHS Classification:

Serious eye damage/eye irritation

Category 2A

Specific target organ toxicity-single exposure:

Category 3 (central nervous system)

GHS Label element

Hazard Pictograms:



Signal Word: Warning

Hazard Statements:

H302: Harmful if swallowed

H315: Causes skin irritation

H319: Causes serious eye irritation

H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

Precautionary Statements

Prevention:

P102: Keep out of reach of children

P103: Read label before use

P201: Obtain special instructions before use

P202: Do not handle until all safety precautions have been read and understood

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

P261: Avoid breathing dust/fume/vapours/spray

P264: Wash thoroughly after handling

P270: Do not eat, drink, or smoke when using this product

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention

P305 + P313 +P337 + P338 + P 351 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

P302 + P352: IF ON SKIN: Wash with soap and water.

P332 + P313: If skin irritation occurs; Get medical advice/attention

P362: Take off contaminated clothing and wash before reuse.

P304 + P 340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312: Call a POISON CENTER/doctor/if you feel unwell

Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed

P405: Store locked up

Disposal:

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional Information:

Causes mild skin irritation.

3. Composition/information on ingredients:

Dipropylene glycol n-butyl ether, CAS 29911-28-2, 5 wt 1-3%

Titanium Dioxide, 13643-67-7, % wt-0-35%

Carbon Black, 1333-86-4, % wt-0-3.5%

Iron Oxide, 1309-37-1, % wt-0-5%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First Aid Measures:

Eye Contact

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

Move individual away from exposure. Immediately flush eyes with large quantities of clean water for at least 15 minutes. Get immediate medical attention

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops or persists

Inhalation

Remove victim to fresh air. Keep warm and quiet. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. GET IMMEDIATE MEDICAL ATTENTION.

Ingestion (Swallowed)

Do not induce vomiting. Potential for aspiration if swallowed. Never give anything by mouth to an unconscious person. GET IMMEDIATE MEDICAL ATTENTION.

Most important symptoms and effects, both acute and delayed.

Most important Symptoms and Effects Irritating to eyes, respiratory system and skin. Drowsiness.

Indication of any immediate medical attention and special treatment needed.

Notes to Physician Treat symptomatically

5. Fire-Fighting Measures

Suitable Extinguishing Media

Carbon dioxide (CO₂), foam, dry chemical, water spray. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Hazardous combustion products: Carbon monoxide, Carbon dioxide (CO₂),
Nitrogen Oxides (NO_x), Isocyanates

Combustion/Explosion Hazards:

This material will not burn unless it is evaporated to dryness. Closed containers may rupture when exposed to extreme heat. Air oxidation of this product may cause it to spontaneously combust. To avoid spontaneous combustion, prevent residue buildup and soak soiled rags, spray-booth filter and over-spray in a closed water-filled metal container.

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

Protective equipment and precautions for firefighters:

Wear self contained breathing apparatus (SCBA) and full fire fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazard while extinguishing the blaze. Use water spray to cool fire-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures.

Personal precautions: Evacuate personnel to safe areas. Use person protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

Environmental precautions: Prevent further leakage or spillage, if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Methods and material for containment and clean up:

Methods for containment: Prevent spilled form 1) contamination in soil, 2) entering sanitary sewers, and drainage systems, and 3) entering bodies of water or ditches that lead to waterways. Prevent spreading over a wide area (e.g. by containment or oil barriers)

Methods for clean-up Soak with inter absorbent material (e.g., sand, silica gel, acid binder, universal binder, sawdust)

7. Handling and storage

Precautions for safe handling

Handling. Avoid breathing vapors or mists. Avoid contact with eyes, skin and clothing. Take off contaminated clothing and wash before reuse. Wash hands before breaks and immediately after handling the product. Use with adequate. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities.

Storage Keep from freezing. Keep containers tightly closed. Keep in a place.

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

8. Exposure controls/Personal Protection

CAS-No	Components	Value type (Form of Exposure)	Control parameters/ Permissible concentration	Basis
29911-28-2	dipropylene Glycol, n-butyl-	TWA (Aerosol)	10 mg/m3	DOW IHG

Appropriate Engineering Controls

Engineering controls: Use general ventilation to maintain airborne concentration to levels that are below regulatory and recommended occupation exposure limits. Good general ventilation should be sufficient to control airborne levels of irritating vapors. Local ventilation may be required during certain operations.

Individual protection measures, such as personal protective equipment.

Eye/face protection: Safety glass with side-shield., if splashes are likely to occur. Tight sealed safety goggles. Ensure that eyewash stations and safety showers are close to the workstation location.

Skin Protections: Gloves made of butyl rubber. Please observe the instructions regarding permeability and breakthrough time which are proved by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Chemical resistant apron, boots.

Respiratory protection: None required if hazards have been assessed and airborne concentrations are maintained below the exposure limits listed in Section 8. Wear an approved air-purifying respirator with organic vapor cartridges where airborne concentrations may exceed exposure limits in Section 8. Use an approve positive-pressure air-supplied respirator with emergency escape provisions if there is any potential from an uncontrolled release, airborne concentrations are not know, or any other circumstances where air-purifying respirators may not provide adequate protect.

General hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	Various colors
Odor	mild amine

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

Odor Threshold	No information available
Physical state	liquid
pH	7.5-9
Flashpoint	> 93 °C
Autoignition Temperature	No information available
Boiling range	100-202 °C
Melting point/freezing point	No information available
Flammability Limit in Air	
Lower	No information available
Upper	No information available
Specific Gravity	1.04
Solubility	Dispersible in water
Evaporation Rate	< 1 (BuAC =1)
Vapor Pressure	17.5 mm Hg @ 20 °C
Vapor Density	> 1 (Air =1)
Percent Volatile	70
VOC content	< 275 g/l-2.29 lbs/gal
Viscosity	7000 cps
Partition Coefficient (n-octanol/water)	No information available
Decomposition Temperature	No information available.

10. Stability and Reactivity

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Hazardous Polymerization does not occur.

Conditions to Avoid

Freezing temperatures, Contamination by those materials referred to under incompatible materials.

Incompatible materials: Strong acids. Strong bases. Strong oxidizing agents. Reducing agents.

Hazardous Decomposition Products: Carbon monoxide. Carbon dioxide (CO₂) Hydrocarbons, Nitrogen oxides (NO_x), Isocyanates

11. Toxicological Information

Information on likely routes of exposure

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

Primary Routes of Entry Skin contact, Ingestion, Inhalation, Eye Contact, skin absorption

Acute toxicity

29911-28-2

Oral LD50	3700 mg/kg (rat)
Dermal LD50	>2000 mg/kg (rat)
Inhalation LC50	Not determined, No deaths at this concentration. LCO, 4h, Aerosol, rat > 2.04 mg/l

Information on toxicological effects

Symptoms: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effect from short and long-term exposure.

Eyes: Causes serious eye irritation

Skin: Mild skin irritant. Repeated exposure may cause skin dryness or cracking. Harmful by skin absorption

Inhalation: Inhalation of vapors in high concentration may cause irritation of respiratory system. Inhalation of high vapor concentrations can cause CNS-depression and narcosis.

Ingestion: Ingestion (swallowing) may irritate the mouth, throat and stomach. Ingestion is not an anticipated route of exposure for this material in industrial use.

Irritation: Irritating to eyes, respiratory system and skin.

Corrosivity: Not corrosive.

Sensitization: Not sensitizing

Carcinogenicity: Group A4-Not classifiable as a human carcinogen.

Target Organs: Eyes, central vascular system (CVS), kidney, liver, central nervous system (CNS), and respiratory system.

12. Ecological Information:

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

29911-28-2

LC50-Fish (Poecilia reticulata (guppy), static test, 96h, 841 mg/l

LC50-, Daphnia magna (water flea), static test, 48h, immobilization, > 1,000 gm/l

OECD 301E, Biodegradation Test, 91%, 28d

OECD 301A, Biodegradation Test, 95%, 28d

OECD 302B, Biodegradation Test, 96%, 28d

Indirect Photodegradation with OH Radicals

Rate constant, $4.97E-11$ cm³/s, atmospheric half life, 2.6h, Method-estimated

Theoretical oxygen demand-2.35mg/mg

Bioaccumulative potential-low, (BCF < 100 or Log Pow < 3)

Partition coefficient, n-octanol/water (log Pow): 1.523 (estimated)

Mobility in Soil, potential is very high (Koc between 0 and 50)

Partition coefficient, soil organic carbon/water (Koc); 10-21 Estimated

Henry's Law Constant (h): $3.78E-07$ atm*m³/mole 25 °C, estimated.

Do not empty into drains; dispose of this material its container in a safe way. Avoid dispersal of spilled material and runoff and runoff and contact with soil, waterways, drains and sewers.

13. Disposal Considerations

Disposal methods

Disposal Considerations: NOT A RCRA HAZARDOUS WASTE. When discarded in its purchased form, this material would not be regulated as a RCRA Hazardous waste under 40 CFR 261.

Contaminated packaging:

Empty remaining contents.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty container.

Empty containers should be taken for local recycling, recovery or waste disposal.

14. Transport Information

DOT: Not regulated

POLOPLAZ WATER BASED PAINT

SDS: 5/11/15

Replaces: 01/18/12

Canada (TDG): Not Regulated.

IATA: Not Regulated

IMDG: Not Regulated

15. Regulatory information

International Inventories

TSCA: United States: Yes-All components are listed or exempt

DSL: Canada Yes-All components are listed or exempt

Federal Regulations

California Proposition 65: This product does not contain a chemical know to the state of California to cause cancer or reproductive harm.

16. Other information

NFPA: Health: 1 Flammability: 10 Reactivity: 0

We recommend containers be either professionally reconditioned for reuse by certified firms or properly disposed of by certified firms to help reduce the possibility of an accident. Disposal of containers should be in accordance with applicable Federal, State, and Local laws and regulations. Empty drums should not be given to individuals.

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or correctness.

The conditions of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.